


<h2 style="margin: 0;">ULTRASONIC DIGITAL THICKNESS GAUGE</h2>	Model: <i>indi</i> 6159																												
<p>Suitable for measuring thickness of Pipes, Rods, Plates, etc. of material like steel, cast iron, aluminium, red copper, brass, zinc, quartz glass, polyethylene, PVC, gray cast iron, nodular cast iron, etc.</p>																													
<p>Specification:</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>Display</td><td>4 Digit 10mm LCD</td></tr> <tr><td>Thickness Range</td><td>1.5 - 200mm (45mm Steel)</td></tr> <tr><td>Accuracy</td><td>±(1.0%+0.2mm),</td></tr> <tr><td>Resolution</td><td>0.1 mm</td></tr> <tr><td>Sensor Type</td><td>Ultrasonic, 5 MHz</td></tr> <tr><td>Sensitivity</td><td>High power of emission & broadband of receiving sensitivity</td></tr> <tr><td>Unit Selection</td><td>mm & inch Switchable</td></tr> <tr><td>Material Type</td><td>11 types of material</td></tr> <tr><td>Material Selection</td><td>By Switch</td></tr> <tr><td>Sensor Head</td><td>8mm Diameter x 28mm (34" Sensor Cord Length)</td></tr> <tr><td>Calibration Block</td><td>Provided</td></tr> <tr><td>Accessories</td><td>Carrying case, Oil Sachet</td></tr> <tr><td>Aux. Supply</td><td>4 x 1.5V AA Size Battery</td></tr> <tr><td>Cabinet Size</td><td>161 X 69 X 32mm ABS Plastic</td></tr> </table>		Display	4 Digit 10mm LCD	Thickness Range	1.5 - 200mm (45mm Steel)	Accuracy	±(1.0%+0.2mm),	Resolution	0.1 mm	Sensor Type	Ultrasonic, 5 MHz	Sensitivity	High power of emission & broadband of receiving sensitivity	Unit Selection	mm & inch Switchable	Material Type	11 types of material	Material Selection	By Switch	Sensor Head	8mm Diameter x 28mm (34" Sensor Cord Length)	Calibration Block	Provided	Accessories	Carrying case, Oil Sachet	Aux. Supply	4 x 1.5V AA Size Battery	Cabinet Size	161 X 69 X 32mm ABS Plastic
Display	4 Digit 10mm LCD																												
Thickness Range	1.5 - 200mm (45mm Steel)																												
Accuracy	±(1.0%+0.2mm),																												
Resolution	0.1 mm																												
Sensor Type	Ultrasonic, 5 MHz																												
Sensitivity	High power of emission & broadband of receiving sensitivity																												
Unit Selection	mm & inch Switchable																												
Material Type	11 types of material																												
Material Selection	By Switch																												
Sensor Head	8mm Diameter x 28mm (34" Sensor Cord Length)																												
Calibration Block	Provided																												
Accessories	Carrying case, Oil Sachet																												
Aux. Supply	4 x 1.5V AA Size Battery																												
Cabinet Size	161 X 69 X 32mm ABS Plastic																												
																													

<h2 style="margin: 0;">ULTRASONIC DIGITAL THICKNESS GAUGE</h2>	Model: <i>indi</i> 6158																																
<p>Suitable for measuring thickness of Pipes, Rods, Plates, etc. of material like steel, cast iron, aluminium, red copper, brass, zinc, quartz glass, polyethylene, PVC, gray cast iron, nodular cast iron, etc.</p>																																	
<p>Specification:</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>Display</td><td>4 Digit Large LCD</td></tr> <tr><td>Thickness Range</td><td>1.2 - 200mm (45mm Steel) / 0.04 – 7.87 inch</td></tr> <tr><td>Accuracy</td><td>±(0.5%+0.1mm),</td></tr> <tr><td>Resolution</td><td>0.1 mm / 0.001 inch</td></tr> <tr><td>Sensor Type</td><td>Ultrasonic, 5 MHz</td></tr> <tr><td>Sensitivity</td><td>High power of emission & broadband of receiving sensitivity</td></tr> <tr><td>Unit Selection</td><td>mm & inch Switchable</td></tr> <tr><td>Material Type</td><td>11 types of material & 500 ~ 9000m/s velocity</td></tr> <tr><td>Material Selection</td><td>By Switch</td></tr> <tr><td>Sensor Head</td><td>8mm Diameter x 28mm (34" Sensor Cord Length)</td></tr> <tr><td>RS 232 Output</td><td>Provided</td></tr> <tr><td>Software & Cable</td><td>Optional</td></tr> <tr><td>Calibration Block</td><td>Provided</td></tr> <tr><td>Accessories</td><td>Carrying case, Oil Sachet</td></tr> <tr><td>Aux. Supply</td><td>4 x 1.5V AAA Size Battery</td></tr> <tr><td>Cabinet Size</td><td>120 X 62 X 30mm ABS Plastic</td></tr> </table>		Display	4 Digit Large LCD	Thickness Range	1.2 - 200mm (45mm Steel) / 0.04 – 7.87 inch	Accuracy	±(0.5%+0.1mm),	Resolution	0.1 mm / 0.001 inch	Sensor Type	Ultrasonic, 5 MHz	Sensitivity	High power of emission & broadband of receiving sensitivity	Unit Selection	mm & inch Switchable	Material Type	11 types of material & 500 ~ 9000m/s velocity	Material Selection	By Switch	Sensor Head	8mm Diameter x 28mm (34" Sensor Cord Length)	RS 232 Output	Provided	Software & Cable	Optional	Calibration Block	Provided	Accessories	Carrying case, Oil Sachet	Aux. Supply	4 x 1.5V AAA Size Battery	Cabinet Size	120 X 62 X 30mm ABS Plastic
Display	4 Digit Large LCD																																
Thickness Range	1.2 - 200mm (45mm Steel) / 0.04 – 7.87 inch																																
Accuracy	±(0.5%+0.1mm),																																
Resolution	0.1 mm / 0.001 inch																																
Sensor Type	Ultrasonic, 5 MHz																																
Sensitivity	High power of emission & broadband of receiving sensitivity																																
Unit Selection	mm & inch Switchable																																
Material Type	11 types of material & 500 ~ 9000m/s velocity																																
Material Selection	By Switch																																
Sensor Head	8mm Diameter x 28mm (34" Sensor Cord Length)																																
RS 232 Output	Provided																																
Software & Cable	Optional																																
Calibration Block	Provided																																
Accessories	Carrying case, Oil Sachet																																
Aux. Supply	4 x 1.5V AAA Size Battery																																
Cabinet Size	120 X 62 X 30mm ABS Plastic																																
																																	

**RS 232
Output**

<p style="font-size: 24px; color: red; margin: 0;">Source 1 INSTRUMENTS</p> <p style="margin: 0;">Plot No. L/715/10, 40 Shed Area, GIDC, Vapi – 396195. Gujarat. India.</p> <p style="margin: 0;">Tel: (0260) 325 1066 Fax: (0260) 2401654 Mob: 93770 29027 / 98244 64050</p> <p style="margin: 0;">Email: sales@source1in.com source1in@indiatimes.com URL: www.source1in.com</p> <p style="margin: 0; font-size: 12px;">Branch Offices: Rajkot Baroda Surat Ahmedabad Chandigarh Nashik Pune Coimbatore</p>	<p style="font-size: 24px; margin: 0;">3 YEAR* REPLACEMENT WARRANTY</p>
--	--