




PORTABLE THERMOMETER WITH SENSOR		Model: <i>indi</i> 6321
Specification:		
Display	1999 Count LCD	
Range	-50 to 1300°C	
Resolution	1°	
Accuracy	±0.5% of Full Scale	
Sensor	Suitable for Cr/Al ('k') type sensor	
Battery	9V Battery	
Sensor Type	Handle type Cr/Al sensor Leaf or Needle	
Enclosure	Portable (Hand Held) type	
Power On/Off	Switch Provided	
Carrying Case	Provided	

PORTABLE THERMOMETER WITH SENSOR		Model: <i>indi</i> 6322
Specification:		
Display	3999 Count Full Icon LCD	
Range	-50 to 300.0°C (-58 to 572°F)	
Resolution	0.1°	
Accuracy	±1°	
Sensor	Built in with indicator	
Battery	1.5V Battery	
Memory	Max. / Min	
Alarm	Hi / Lo Provided	
Table Stand	Provided	
Enclosure	Portable (Hand Held) type	

FLAMEPROOF INDICATOR / CONTROLLER		Model: <i>indi</i> 6346
Specification:		
Display	1999 Count LED	
Range	As Required	
Input	Pt-100 RTD, 'J'/'K' Thermocouple, 4-20mADC/0-10VDC/0-20mADC Analogue Input	
No. of Inputs	1, 6 or 12	
Resolution	0.1 / 1	
Accuracy	±0.5% of Full Scale	
Set Point	1 or 2 (Controller Only)	
Battery	9V Battery	
Output	Relay / SSR (Controller Only)	
Enclosure	CMRI Dhanbad Certified for Gas Group IIA & IIB	
Supply	230±10%VAC	

<h2 style="color: red;">Source 1</h2> <p>INSTRUMENTS</p> <p>Plot No. L/715/10, 40 Shed Area, GIDC, Vapi – 396195. Gujarat. India. Tel: (0260) 325 1066 Fax: (0260) 2401654 Mob: 93770 29027 / 98244 64050 Email: sales@source1in.com source1in@indiatimes.com URL: www.source1in.com Branch Offices: Rajkot Baroda Surat Ahmedabad Chandigarh Nashik Pune Coimbatore</p>	<p>3 YEAR* REPLACEMENT WARRANTY</p>
---	--