

TEMP. / HUMIDITY TRANSMITTER	Model: <i>indi</i> 6396
-------------------------------------	-------------------------




Specification:

Temp. Range	0 – 65°C
Accuracy	±0.6°C
Humidity Range	5% - 95% RH
Accuracy	±3%
Humidity Output Voltage	10mV / %RH
Temperature Output Voltage	10mV / °C
Operating Supply	6 – 16VDC
Output Load	100kOhms typical
Operating Environment	0 – 65°C / 5% - 95% RH

WALL MOUNTED TEMP. / HUMIDITY INDICATOR	Model: <i>indi</i> 6397
--	-------------------------

Specification:

Temp. Range	0 – 65°C	
Accuracy	±0.6°C	
Humidity Range	5% - 95% RH	
Accuracy	±3%	
Display	3 ½ Digit Dual LCD, 12.5mm H	
Oper. Supply	24VDC or 230VAC	
Optional Output	4-20mADC Output	
Oper. Temp.	0 – 65°C	
Oper. Humidity	5% - 95% RH	
Enclosure Type	IP 66 Enclosure (weather proof) ABS	
Enclosure Size	120 x 80 x 85 mm. (L x B x H)	
Option	Built in Sensor or Wired Sensor	

<p style="font-size: 24px; color: red; margin: 0;">Source 1 INSTRUMENTS</p> <p style="margin: 0;">Plot No. L/715/10, 40 Shed Area, GIDC, Vapi – 396195. Gujarat. India.</p> <p style="margin: 0;">Tel: (0260) 325 1066 Fax: (0260) 2401654 Mob: 93770 29027 / 98244 64050</p> <p style="margin: 0;">Email: sales@source1in.com source1in@indiatimes.com URL: www.source1in.com</p> <p style="margin: 0; font-size: 12px;">Branch Offices: Rajkot Baroda Surat Ahmedabad Chandigarh Nashik Pune Coimbatore</p>	<p style="font-size: 24px; margin: 0;">3 YEAR*</p> <p style="font-size: 24px; margin: 0;">REPLACEMENT</p> <p style="font-size: 24px; margin: 0;">WARRANTY</p>
--	--